

AXIS T92E Housing Series

Smart features for wide ranging of environments



- > Dual shell
- > IP66- and NEMA 4X-rated
- > IK10-rated
- > One cable installation
- > Arctic Temperature Control

AXIS T92E Housing Series protects the Axis network camera in adverse indoor and outdoor conditions.

AXIS T92E Housing Series is available in two models: AXIS T92E05 Protective Housing and AXIS T92E20 Outdoor Housing.

AXIS T92E20 features an internal shell for storing heat in cold environments. Fan ventilation for hot environments transfers excess to the outer chassis for efficient cooling.

AXIS T92E05/T92E20 feature IP66 and NEMA 4X protection rating against the ingress of dust, windblown dust, rain, high pressure water jets from any direction, hose-directed water, and damage from external ice formation. In addition, they are IK10- rated for protection against impact and vandal acts.

Easy and quick installation using either Power over Ethernet or High Power over Ethernet connection. The network cable is further protected in the wall mount to enhance the vandal protection.

The Arctic Temperature Control functionality ensures that the cameras can start up even at -40°C (-40°F) following a power failure.

Various brackets and accessories are available for AXIS T92E Housing Series, such as ceiling and wall brackets, column mounts and adapters. AXIS T92E Series comes with a wall bracket with an internal cable channel and ball joint.



Technical Specifications - AXIS T92E Housing Series

Models	AXIS T92E05 Protective Housing AXIS T92E20 Outdoor Housing	Approvals	AXIS T92E05: IEC/EN 60529 IP66, NEMA 250 Type 4X, IEC 60068-2-6, IEC 60068-2-27, IEC/EN 62262 IK10 AXIS T92E20: EN 55022 Class B, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, C-tick AS/NZS CISPR 22, EN 60950-22, IEC/EN 60529 IP66, NEMA 250 Type 4X, IEC 60068-2-6, IEC 60068-2-27, IEC/EN 62262 IK10
General		Weight	AXIS T92E05: 2.4 kg (5.1 lb) AXIS T92E20: 2.5 kg (5.5 lb)
Supported cameras	AXIS T92E05: Indoor: AXIS M1103/M1104 Indoor/Outdoor: AXIS M1113/M1114, AXIS P13 Series, AXIS Q16 Series, AXIS Q1755 AXIS T92E20: AXIS M1113/M1114, AXIS P13 Series, AXIS Q16 Series, AXIS Q1755	Included accessories	VT Wall brackets, Sunshield, Installation Guide, Screw driver torx 20 AXIS T92E20: 2x short Ethernet cables
Casing	Aluminium casing, polycarbonate sunshield and cable cover IP66- and NEMA 4X-rated, IK10 impact-resistant aluminum enclosure	Warranty	Axis 3-year warranty, www.axis.com/warranty
Power	AXIS T92E05: Not required AXIS T92E20: Power over Ethernet (PoE) IEEE 802.3af or High Power over Ethernet (High PoE) Power supply not included	More information is available at www.axis.com	
Environment	Indoor/Outdoor		

	AXIS T92E05 Protective Housing	AXIS T92E20 Outdoor Housing
Operating conditions	AXIS Q1755: PoE IEEE 802.3af: 0 °C to 45 °C (32 °F to 113 °F) Humidity 15-100% RH (condensing) AXIS P13/Q16 Series: PoE IEEE 802.3af: 0 °C to 50 °C (32 °F to 122 °F) Humidity 15-100% RH (condensing) AXIS M11 Series: PoE IEEE 802.3af: -20 °C to 50 °C (-4 °F to 122 °F) Humidity 15-100% RH (condensing)	AXIS Q1755: PoE IEEE 802.3af: -30 °C to 45 °C (-22 °F to 113 °F) High PoE IEEE 802.3at: -40 °C to 45 °C (-40 °F to 113 °F) Humidity 15-100% RH (condensing) AXIS P13/Q16 Series: PoE IEEE 802.3af: -30 °C to 50 °C (-22 °F to 122 °F) High PoE IEEE 802.3at: -40 °C to 50 °C (-40 °F to 122 °F) Humidity 15-100% RH (condensing) AXIS M1113/M1114: PoE IEEE 802.3af: -30 °C to 50 °C (-22 °F to 122 °F) High PoE IEEE 802.3at: -35 °C to 50 °C (-31 °F to 122 °F) Humidity 15-100% RH (condensing)

Dimensions

- Without sunshield
- With sunshield
- Wall mount bracket
- Wall mount bracket, backside

Optional accessories

- AXIS T91A47 Pole Mount
- AXIS T98A16-VE
- AXIS T90A Illuminators
- Scan for a complete list of accessories www.axis.com/products/cam_housing/t92e/